

SmartProx™  
G1396



Geoffrey's SmartProx Proximity Card offers the thin card features of the ISOProx II and DuoProx II Proximity Cards in a package designed for implantation of contact smart technology.

## APPLICATIONS

- Meets customer requirements for network access, data security, debit transaction, parking, benefit information storage, photo ID and proximity access control with a single card.
- Provides physical access to data processing areas, as well as logical access to corporate databases.
- Ability to carry a complete biometric identifier for critical perimeter access control while providing the ease of use proximity elsewhere.
- Note: applications of smart chip depend on size of chip memory and software. Geoffrey does not manufacture smart chip modules.
- Accommodates custom graphics, direct image printing, magnetic stripes, bar codes and contact smart modules.

## FEATURES

- **Proven, reliable technology** The read range is extremely consistent and is unaffected by body shielding or variable environmental conditions, even when close to keys and coins.
- **Thin** Easily carried with credit cards in wallet or purse.
- **Photo compatibility** Can be directly printed with dye-sublimation video image printers.
- **Cross-reference** A cross-reference list correlating the external card number and the programmed ID number is standard for easy system administration. External numbering matching the encoded numbers is available.
- **Long life** Passive, no-battery design allows an infinite number of reads.
- **Durability** Strong, flexible and resistant to cracking and breaking.
- **Custom Graphics** Custom multicolor graphics are available.

## SPECIFICATION

- **Typical maximum\* read range:** ProxPoint™ reader up to 1.5" (3.5 cm); MiniProx™ Card up to 2.5" (6.2 cm); ThinLine® reader up to 2.5" (6.2 cm); ProxPro® reader up to 5" (12.5 cm); ProxPro® Plus reader up to 6" (14.0 cm); MaxiProx® reader up to 15" (35.5 cm)
- **Dimensions:** 2.125" x 3.375" x 0.031" max. (5.40 x 8.57 x 0.079 cm)
- **Card construction:** Thin, flexible polyvinyl chloride (PVC) laminate.
- **Operating temperature:** -50° to 160° F (-45° to 70° C)
- **Operating humidity:** 5-95% relative humidity non-condensing
- **Weight:** 0.24 oz. (6.8 gm)
- **Options:**
  - External card numbering
  - Slot punch (horizontal and vertical)
  - Custom graphics

\*Depending on local installation conditions.



2 Cranberry Road  
P.O. Box 5907  
Parsippany, NJ 07054  
Tel: 973.299.1300  
Toll Free: 800.604.3633  
Fax: 973.299.9799  
E-mail: [sales@geoffreyaccess.com](mailto:sales@geoffreyaccess.com)  
Web: [www.geoffreyaccess.com](http://www.geoffreyaccess.com)